

**MOTOGENERATORE
GENERATING SET**

MG 275 SS-V



**MANUALE D'ISTRUZIONE
OWNERS MANUAL**

Motogeneratore - Generating Set MG 275 SS-V

1. CARATTERISTICHE TECNICHE / TECHNICAL SPECIFICATIONS

1.1 GENERATORE / GENERATOR

Tipo	Sincrono / Synchronous	Type
Potenza trifase (d'emergenza) (*)	275 kVA 415/240 V	Three phase stand-by power (*)
Potenza trifase (continua) (**)	247,5 kVA 415/240 V	Three phase prime power (**)
Potenza monofase	91,5 kVA 240 V	Single phase power
Frequenza	50 Hz	Frequency
Cos φ	0,8	Cos φ
Classe isolamento	H	Insulation class
Grado di protezione	IP 23	Mechanical protection

1.2 MOTORE / ENGINE

Tipo motore	VOLVO Penta TAD 740 GE	Make/Type
Numero cilindri	6	Number of cylinders
Cilindrata	7280 cm ³	Displacement
Potenza	241,9 kW (329 HP)	Power
Velocità	1500 r.p.m.	Engine speed
Raffreddamento	Acqua – Water	Cooling
Carburante	Diesel	Fuel
Capacità coppa olio	24 l	Oil sump capacity
Avviamento	Elettrico – Electric	Starting system
Consumo orario @75%	43,023 l/h	Hour fuel consumption @ 75%

(*) Potenza per impiego d'emergenza secondo DIN 6271 B.

(**) Potenza per servizio continuo 24 ore su 24 sovraccaricabile del 10% per 1 ora ogni 12 ore secondo DIN 6271-A e ISO 3046-I.

(*) Stand-by power an emergency situation according to DIN 6271 B.

(**) Prime power: maximum continuous power with an intermittent 10% overload capacity according to DIN 6271-A and ISO 3046-I

Motogeneratore - Generating Set MG 275 SS-V

1.3 CARATTERISTICHE GENERALI / GENERAL FEATURES

Potenza acustica	92 Lwa	Noise level
Batteria	2 x 120 Ah – 12 V	Battery
Capacità serbatoio carburante	567 l	Fuel tank capacity
Dimensioni (Lu. x La. x H.)	3900x1400x2320 mm	Dimensions (L. x W. x H.)
Peso a vuoto	3300 kg	Dry Weight

250 Kva /17

GENSET FEATURES

50Hz 415V

Double dipped Alternator.

Spark Arrestor muffler.

Battery isolator switch.

Mechanical 4 poles circuit breaker with electronic release device.

Earth leakage device.

Earth leakage relay bypass.

Key start

Elcos SPG120 display

Fuel tank inspection hatch.

5 pole hard wire connections.

Emergency stop button.

Central lifting eye.

Fork lift pockets.

Lube oil drain pump.

Coolant drain pipe.

Fuel/ water separator.

3 way fuel change over valve.

Owners manual.