

GenSet



MG 70 S-DR



GEN SET S.p.a.

Via Stazione,5 - 27030 Villanova D' Ardenghi (Pavia) Italy

Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244

E-mail: genset@genset.it - internet: [//www.genset.it](http://www.genset.it)

MG 70 S-DR

SILENCED THREE-PHASE POWER GENERATOR / OUTPUT POWER 66 KVA
THREE-PHASE AND 22 KVA SINGLE-PHASE / DIESEL ENGINE 1500 RPM

Gen Set Features	<ul style="list-style-type: none"> + Controller (DSE 6120) with digital display for full monitoring of generator parameters: 3-phase generator voltage, 3-phase mains voltage, battery voltage, ammeter, frequency, hour meter, oil pressure, engine temperature, fuel level, fail to start; with auto engine protection shutdown system in case of: <ul style="list-style-type: none"> - fail to start - emergency stop - low oil pressure - low fuel level - high coolant temperature - oil pressure sender open circuit - over/under voltage - over/under frequency - open door + Inlet air restriction alarm 	<ul style="list-style-type: none"> + Fuel/Water separator alarm + Adjustable Earth leakage Relay + 4 poles main Circuit Breaker + Three-phase output terminal board + Set mounted distribution board with three and single-phase outlets protected by main Circuit Breakers + Emergency STOP button + Automatic Voltage Regulator + Manual oil sump pump + Battery switch + Central lifting eye + Fork-lift pockets + Bunded base to retain all liquids + Remote control terminal board + ATS terminal board + Fuel Filter/Water separator
Gen Set Options (available as factory options)	<ul style="list-style-type: none"> + 60 Hz version + Versions with different voltages + Electronic frequency regulator + Engine water heaters powered by mains 230 V - 50 Hz 	<ul style="list-style-type: none"> + Spark arrester muffler + Long run fuel tank (24h) complete with bunded base + Separate tank facility c/w quick release coupling
Accessories on Request	<ul style="list-style-type: none"> + Two-wheels site tow undercarriage (GRT2W) + Remote Start/Stop kit by cable (20/50 m) + Auto Transfer Switch (ATS) panel complete with battery charger for auto-start operation 	
Noise Level	+ Lwa 95 (70 dB a 7 m)	
AC Generator 50 Hz	<ul style="list-style-type: none"> + Type: synchronous + Three-phase power (stand by): 66 kVA - 400 V + Three-phase power (prime): 60 kVA - 400 V 	<ul style="list-style-type: none"> +Single-phase power (max.): 22 kVA - 230 V +Power Factor: cos ϕ 0,8
Diesel Engine 1500 rpm	<ul style="list-style-type: none"> + Type: Deutz BF4M 2012 - turbocharged - 4 cyl. 70,6 HP (52 kWm) - 4040 cm³ + Fuel: diesel + Cooling system: water + Starting system: electric + Fuel tank capacity: 170 l + Fuel consumption @ 75%: 10,2 l/h 	
Other Features	<ul style="list-style-type: none"> + Insulation Class: H + Ambient temperature: 40 °C + Altitude: 1000 mt + Mechanical Protection: IP 23 	<ul style="list-style-type: none"> + Dimensions (L x W x H): 2400 x 950 x 1500 mm + Dry weight: 1320 kg + Total weight: 1460 kg

Generator set in designed to operate in ambient temperature up to 40 °C and 1000 mt altitude - For higher values of temperature and altitude please consult factory to check available power.