

MG 15/10 I-L

THREE-PHASE POWER GENERATOR / OUTPUT POWER **15 KVA**
THREE-PHASE AND **10 KVA** SINGLE-PHASE /
DIESEL ENGINE **3000 RPM**

Gen Set Features	<ul style="list-style-type: none">+ DAS, auto engine protection shutdown system with warning lights in case of:<ul style="list-style-type: none">- battery charger failure- low fuel level- low oil pressure+ Automatic idle device when no load is connected+ 12V built-in battery with electric start+ Engine hourmeter+ Fuel level gauge	<ul style="list-style-type: none">+ 1 x 32A, 400 V - 50 Hz three-phase EEC socket+ 1 x 32A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker+ 1 x 16A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker+ Earth Leakage Circuit Breaker (ELCB)+ Voltmeter+ Central lifting eye+ Trolley: two-wheels and handles
Gen Set Options (available as factory options)	<ul style="list-style-type: none">+ Versions with different voltages+ Spark arrester muffler+ AMF/ATS panel for auto start operation	
Accessories on Request	<ul style="list-style-type: none">+ Two-wheels site tow undercarriage (GRT2W)	
Noise Level	<ul style="list-style-type: none">+ LWA 99 (74 dB at 7m)	
AC Generator 50 Hz	<ul style="list-style-type: none">+ Type Gen Set asynchronous self-excited and self-protected+ Three-phase power (stand by) 15 kVA - 400 V+ Three-phase power (prime) 13,5 kVA - 400 V+ Single-phase power (max.) 10 kVA - 230 V+ Power Factor 0,8	
Diesel Engine 3000 rpm	<ul style="list-style-type: none">+ Type Lombardini 9LD625-2 - 2 cyl. - 28,5 HP (21 kWm) - 1248 cm³+ Fuel diesel+ Cooling system air+ Starting system electric+ Fuel tank capacity 38 l+ Fuel consumption @ 75% 4,7 l/h	
Other Features	<ul style="list-style-type: none">+ Insulation Class F+ Mechanical Protection IP 23+ Dimensions (L x W x H) 1400 x 630 x 1023 mm (trolley not included)+ Dry Weight 380 kg	

MG 15/10 I-L

