

## MG 5000 I-Y/E

PORTABLE SINGLE-PHASE POWER GENERATOR /  
OUTPUT POWER **4 KVA** SINGLE-PHASE /  
DIESEL ENGINE **3000 RPM**

<b>Gen Set Features</b>	<ul style="list-style-type: none"><li>+ Low oil pressure and battery charger warning lights</li><li>+ 12V built-in battery with electric start</li><li>+ 2 x 230 V - 50 Hz single-phase Schuko outlets protected by circuit breaker</li><li>+ 1 x 12V DC battery charger outlet protected by fuse</li><li>+ Wheels and handles</li><li>+ Fuel level gauge</li></ul>
<b>Gen Set Options</b> (available as factory options)	<ul style="list-style-type: none"><li>+ Versions with different voltages</li><li>+ 60 Hz version</li></ul>
<b>Accessories on Request</b>	<ul style="list-style-type: none"><li>+ Not available</li></ul>
<b>Noise Level</b>	<ul style="list-style-type: none"><li>+ Lwa 100 (75 dB at 7m)</li></ul>
<b>AC Generator 50 Hz</b>	<ul style="list-style-type: none"><li>+ Type synchronous</li><li>+ Single-phase power (max.) 4 kVA - 230 V</li><li>+ Battery Charger 120 W - 12 V - 10 A - CC</li><li>+ Power Factor 0,8</li></ul>
<b>Diesel Engine 3000 rpm</b>	<ul style="list-style-type: none"><li>+ Type <b>Yanmar L70AE</b> - 1 cyl. - 6,6 HP (4,8 kWm) - 296 cm<sup>3</sup></li><li>+ Fuel diesel</li><li>+ Cooling system air</li><li>+ Starting system electric (and manual)</li><li>+ Fuel tank capacity 3,5 l</li><li>+ Fuel consumption @ 75% 1,3 l/h</li></ul>
<b>Other Features</b>	<ul style="list-style-type: none"><li>+ Insulation Class H</li><li>+ Mechanical Protection IP 23</li><li>+ Dimensions (L x W x H) 720 x 460 x 510 mm</li><li>+ Dry Weight 98 kg</li></ul>

## MG 5000 I-Y/E

