

MG 6000 I-D/AE-Y

SINGLE-PHASE POWER GENERATOR /
OUTPUT POWER **6 KVA** SINGLE-PHASE /
DIESEL ENGINE **3000 RPM**

Gen Set Features

- + Low oil pressure and battery charger warning lights
- + 12V built-in battery with electric start
- + 1 x 32A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker
- + 1 x 12V DC battery charger outlet protected by circuit breaker
- + Voltmeter
- + Fuel level gauge

Gen Set Options (available as factory options)

- + Earth Leakage Circuit Breaker (ELCB)
- + Versions with different voltages
- + 60 Hz version
- + AMF/ATS panel for auto start operation

Accessories on Request

- + Trolley: two-wheels and handles

Noise Level

- + LWA 99 (74 dB at 7m)

AC Generator 50 Hz

- + Type synchronous
- + Single-phase power (max.) 6 kVA - 230 V
- + Battery Charger 180 W - 12 V - 15 A - CC
- + Power Factor 0,8

Diesel Engine 3000 rpm

- + Type **Yanmar L100AE** - 1 cyl. - 10 HP (7,4 kWm) - 406 cm³
- + Fuel diesel
- + Cooling system air
- + Starting system: electric (and manual)
- + Fuel tank capacity 5,5 l
- + Fuel consumption @ 75% 1,7 l/h

Other Features

- + Insulation Class H
- + Mechanical Protection IP 23
- + Dimensions (L x W x H) 920 x 460 x 570 mm
- + Dry Weight 125 kg

MG 6000 I-D/AE-Y

