

MG 6000 Y/AE

PORTABLE SINGLE-PHASE POWER GENERATOR /
OUTPUT POWER **5,4 KW** SINGLE-PHASE /
DIESEL ENGINE **3000 RPM**

Gen Set Features	<ul style="list-style-type: none">+ 12V built-in battery with electric start+ Engine hourmeter+ 1 x 32A, 230 V - 50 Hz single-phase EEC socket+ 1 x 16A, 230 V - 50 Hz single-phase EEC socket+ Main circuit breaker+ Earth Leakage Circuit Breaker (ELCB)+ Voltmeter+ AMF connector / RC connector+ Central lifting eye
Gen Set Options (available as factory options)	<ul style="list-style-type: none">+ Versions with different voltages+ 60 Hz version
Accessories on Request	<ul style="list-style-type: none">+ Trolley: two-wheels and handles+ AMF/ATS panel for auto start operation+ Remote Start/Stop kit by cable (20m)
Noise Level	+ LWA 105 (80 dB at 7m)
AC Generator 50 Hz	<ul style="list-style-type: none">+ Type synchronous+ Single-phase power (max.) 5,4 kW - 230 V+ Power Factor 1
Diesel Engine 3000 rpm	<ul style="list-style-type: none">+ Type Yanmar L100AE - 1 cyl. - 10 HP (7,4 kWm) - 406 cm³+ Fuel diesel+ Cooling system air+ Starting system electric+ Fuel tank capacity 5,5 l+ Fuel consumption @ 75% 1,7 l/h
Other Features	<ul style="list-style-type: none">+ Insulation Class H+ Mechanical Protection IP 23+ Dimensions (L x W x H) 820 x 580 x 610 mm+ Dry Weight 110 kg

MG 6000 Y/AE

