

MG 5000 S-Y

SILENCED SINGLE-PHASE POWER GENERATOR /
OUTPUT POWER **3,4 KW** SINGLE-PHASE /
DIESEL ENGINE **3000 RPM**

Gen Set Features	<ul style="list-style-type: none">+ 12V built-in battery with electric start+ Voltmeter+ Engine hourmeter+ Emergency STOP button+ Earth Leakage Circuit Breaker (ELCB)+ 1 x 32A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker+ 1 x 16A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker+ AMF connector / RC connector+ Central lifting eye		
Gen Set Options (available as factory options)	<ul style="list-style-type: none">+ Versions with different voltages+ 60 Hz version		
Accessories on Request	<ul style="list-style-type: none">+ Trolley: two-wheels and handles+ AMF/ATS panel for auto start operation+ Remote Start/Stop kit by cable (20m)		
Noise Level	+ Lwa 97	(72 dB at 7m)	Homologated in accordance with the "Directive 2000/14/EC"
AC Generator 50 Hz	<ul style="list-style-type: none">+ Type synchronous+ Single-phase power (max.) 3,4 kW - 230 V+ Power Factor 1		
Diesel Engine 3000 rpm	<ul style="list-style-type: none">+ Type Yanmar L70AE - 1 cyl. - 6,6 HP (4,8 kWm) - 296 cm³+ Fuel diesel+ Cooling system air+ Starting system electric+ Fuel tank capacity 10,5 l+ Fuel consumption @ 75% 1,3 l/h		
Other Features	<ul style="list-style-type: none">+ Insulation Class H+ Mechanical Protection IP 23+ Dimensions (L x W x H) 815 x 560 x 730 mm+ Dry Weight 125 kg		

MG 5000 S-Y

 **GenSet**

